

KS – 47B

TOYOTOMI



Product Data Sheet:

Product range	Mobile paraffin heater
Product line	Wick type
Brand	TOYOTOMI
Model	KS – 47B
Color	White
EAN / No. Article	n.a.

Technical Specification:

Burner type		Single combustion
Capacity	kW	5,3
Suitable surface	m ²	23 – 32
Suitable volume	m ³	58 – 80
Fuel consumption	Ltr/hr	0,50
Tank capacity	Ltr	7,5
Burning time tank	hr	15,0
Wick height	mm	8,0
Type of battery		« C »size * 2
Noise level	dB (A)	n.a.
Dimensions	WxDxH mm	440 x 440 x 582
Dimensions carton box	WxDxH mm	460 x 460 x 660
Weight	Kg	11
Weight (gross)	Kg	12
Guarantee	Years	2

TOYOTOMI 65th
Japanese Technology Anniversary since 1949

Toyotomi Europe Sales B.V.
Doornhoek 4025
5465 TD Veghel
The Netherlands
Tel: +31 (0)413 82 02 95
Fax: +31 (0)413 74 50 38
www.toyotomi.eu
info@toyotomi.eu

Accessories:

Manual fuel pump	
Transport cap	n.a.
Instruction manual	EN

CE

Features:

CLEAN COMBUSTION SYSTEM :

This heater can be installed without wires and without exhaust pipes. Toyotomi's state of the art Clean Chamber System maximizes fuel combustion and reduces unwanted emission of gases to an ultimate safety level.

HIGH EFFICIENCY:

The TOYOTOMI heater has 99.99% heat efficiency with Infrared-ray heating.

POWERFUL HEATING OUTPUT:

It offers intense heating output up to 18.200 BTU/h or a convenient 5.3 kWh.

AUTOMATIC IGNITION

The heater is easy to operate, simply by turning the main dial to the right and push the igniter button, activating the ignitor coil.

TRIPLE SAFETY EXTINGUISHER

There are 3 extinguishing methods on the KS – 47B

1. By retracting the wick.
2. By pushing emergency / safety button.
3. Automatic shut-off is activated when the heater is bumped into, or in the event of a tip-over (earthquake safety device).

DOUBLE WALL TANK CONSTRUCTION:

The Double Wall Tank Construction prevents leakage, even when heater tips over for safety.

WICK LIFE EXTENDER:

TOYOTOMI's own patented wick height adjustable design will guarantee you a longer wick life and ultimately a better performance.

MADE IN JAPAN:

Manufactured according to ISO 9000 :2000 standards in Japan, with a 2 year guarantee.