



Product data sheet:

Product range	Portable kerosene heaters
Product line	Wick type
Brand name	ZIBRO made by Toyotomi
Model name	RC - 270
Colour	New Stainless Steel - Noir
EAN Code	4963505710798

Technical specification:

Burner type		Double combustion
Capacity	kW	2,16 – 2,70
Suitable surface	m²	18 – 38
Suitable volume	m ³	45 – 95
Fuel consumption	Ltr/uur	0,225 – 0,281
	g/uur	180 – 225
Tank capacity	Ltr	4,0
Burning time tank	uur	14,2 – 17,7
Wick height	mm	7,5 – 9
Wick type		(vilt) type F
Type battery (not included)		"D" size x 4
Dimensions heater	WxDxH mm	428 * 295 * 513
Dimensions carton box	WxDxH mm	480 * 340 * 570
Nett weight	Kg	9,0
Gross weight	Kg	10,5
Guarantee	Years	4

TÖYÖTÖMİJapanese Technology

Toyotomi Europe Sales B.V. Doornhoek 4025 5465 TD Veghel The Netherlands Tel: +31 (0)413 82 02 95 Fax: +31 (0)413 74 50 38 www.toyotomi.eu info@toyotomi.eu

Accessories:

Manual syphon pump	
Transport cap	
Instructin manual 6 languages	NL/FR/DE/EN/SP/IT











Product Specification



NO INSTALLATION

This heater can be installed without wires and without exhaust pipes. This makes it a very convenient heating source.



CLEAN COMBUSTION

TOYOTOMI's state of the art Double Clean® Chamber System maximizes fuel combustion and reduces unwanted emission gases to ultimate safety level.

COOL-TOP PLATE WITH REDUCED TEMPERATURE



HIGH EFFICIENCY

The TOYOTOMI heater has 99.99% heat efficiency with Infrared-ray heating.



AUTOMATIC IGNITION

The heater is easy to operate, simply by turning the main dial to the right and push the igniter button, activating the 'pumpa' piezo element



AIR QUALITY CONTROL SYSTEM (E-GUARD)

This heater is equipped with a E-Guard air quality control system. The customer is informed when additional ventilation is desired. The heater will be switched off when the room is not ventilated sufficiently.



TRIPLE SAFETY EXTINGUISHER

There are 3 extinguishing methods on the RC-300E

- 1.By retracting the wick.
- 2.By pushing emergency button.
- 3. Automatic shut-off is activated when the heater is bumped into, or in the event of a tip-over (earthquake safety device).



POWERFUL HEATING OUTPUT

It offers intense heating output up to 2,7 kW and by adjusting flame height you can reach a min. mode of 2,50 kW.



WICK LIFE EXTENDER

TOYOTOMI's original patented design. It helps maintain good wick performance and extends useful wick life.



ECONOMICAL

Easy to ignite and low running cost with less fuel.

EASY TO FILL / ANTI LEAKAGE VALVE

Convenient removable fuel tank and a handy syphon comes with the heater. The fuel tank is equipped with a anti-leakage valve which prevents leakage even when the tank is held upside down without the tank cap.