

WICK TYPE RC-300E



Product data sheet

Product range	Portable kerosene heaters
Product line	Wick
Brand name	TOYOTOMI
Model name	RC – 300 E
Colour	Black
EAN code	4963505710767

Technical specification

Burner type	Double Clean	
Capacity	kW max.	3.00
	kW min.	2.52
Suitable space	M ²	22 - 44
	M ³	55 - 110
Fuel consumption	ltr/hr	0.263 – 0.313
Tank capacity	ltr	5.5
Burning time tank	hr	17.5 – 20.9
Wick height	mm	7 - 9
Battery type	"D" size x 4	
Dimensions (w x d x h)	mm	562 x 279 x 502
Weight	kg	11.5
Guarantee	years	2


Accessories

Manual fuel pump


Instruction manual F/D/GB/NL



Gross =
13,0 kg



20 ft = 261 pcs
40 ft = 551 pcs
HQ = 608 pcs



W x D x H =
620 x 330 x 560 mm

Max. stacking height 8 units



TOYOTOMI

Toyotomi Europe Sales B.V.
Doornhoek 4025
5465 TD Veghel
The Netherlands
TEL: +31 (0)413 820295

WICK TYPE RC-300E

Features

■ CLEAN COMBUSTION

TOYOTOMI's state of the art Double Clean® Chamber System maximizes fuel combustion and reduces unwanted emission gases to ultimate safety level.

■ HIGH EFFICIENCY

The TOYOTOMI heater has 99.99% heat efficiency with Infrared-ray heating.

■ NO INSTALLATION

This heater can be installed without wires and without exhaust pipes. This makes it a very convenient heating source.

■ AUTOMATIC IGNITION

The heater is easy to operate, simply by turning the main dial to the right and push the igniter button, activating the 'pumpa' piezo element.

■ TRIPLE SAFETY EXTINGUISHER

There are 3 extinguishing methods on the RC-300E

1. By retracting the wick.
2. By pushing emergency button.
3. Automatic shut-off is activated when the heater is bumped into, or in the event of a tip-over (earthquake safety device).

■ AIR QUALITY CONTROL SYSTEM (E-GUARD)

This heater is equipped with a E-Guard air quality control system. The customer is informed when additional ventilation is desired. The heater will be switched off when the room is not ventilated sufficiently.

■ COOL-TOP PLATE WITH REDUCED TEMPERATURE

■ POWERFUL HEATING OUTPUT

It offers intense heating output up to 10,300 BTU / h or 3.00 kW and by adjusting flame height you can reach a min. mode of 2,50 kW.

■ WICK LIFE EXTENDER

TOYOTOMI's original patented design. It helps maintain good wick performance and extends useful wick life.

■ ECONOMICAL

Easy to ignite and low running cost with less fuel.

■ EASY TO FILL / ANTI LEAKAGE VALVE

Convenient removable fuel tank and a handy syphon comes with the heater. The fuel tank is equipped with a anti-leakage valve which prevents leakage even when the tank is held upside down without the tank cap.